


Low Voltage											
Inverter		Battery			Communication	Cable Supply	Coupling type	Application	Key Features	Firmware Ver.	Installation
Brand of Inverter	Type	US2000B	Phantom-S	US2000B Plus							
Victron	Multi / Quattro in 48V				CAN	RJ45	DC	On-grid	Activation: Immidiately; Force charge: Yes	418/V2.11	Wall mounting
SolaX	SK-SU, SK-TL, SK-BMU				CAN/RS232	RJ45	DCAC	On-grid	Activation: Use PV only; Force charge: Yes		Wall mounting
Goodwe	GW-BP/SBP; GW-ES/EM				CAN	RJ45	DCAC	On-grid	Activation: Yes; Force charge: Yes		Wall mounting
IMEON	IMEON 3.6 &9.12				CAN	RJ45	DCAC	On-grid		V1.7.6.5	Wall mounting
Selectronic	SPMC in 48V				CAN	RJ45	DC	On-grid	Activation: No; Force charge: Yes		Wall mounting
Voltronic	Infinisolar series 48V(1) Axpert series 48V(2)					N/A	DC	On/off-grid	Activation:(1)Yes(2)Manual Force charge: Yes		Wall mounting
Sofar	ME3000SP				RS485(115200)/CAN	RJ45	DC	On-grid	Activation: No; Force charge: Yes	V1.2	Wall mounting
Solis	RHI-3K~5K-48ES				CAN	RJ45	DC	On/off-grid	Activation: Use PV only; Force charge: Yes	90009	Wall mounting
Redback	SH4600				RS485(115200)	RJ45	DCAC	On-grid	Activation: Use PV only(30mins delay);		Vertical
Sungrow	SH5K				CAN	Terminal	DC	On-grid	Activation: 30mins; Force charge: Yes	V13	Wall mounting
GMDE	SolDate 3700TL+BM024				RS485(9600)	RJ45	DCAC	On-grid	Activation: No; Force charge: Yes	V2.0.1	Wall mounting
Dowell	iPower				RS485(9600)/CAN	Terminal	DCAC	On-grid	Activation: Use PV only; Force charge: Yes	V3.03	Wall mounting
High Voltage											
Type		Battery			Communication	Cable Supply	Coupling type	Applicatnio	Key Features	Firmware Ver.	Installation
SolaX	X1/X3-Hybrid HV	Powercube X1/H1			CAN	RJ45	DCAC	On-grid	Activation:Yes Force charge: Yes(SOC<5%)		Wall mounting
Sungrow	SC series	Powercube M1			Customized with additional EMS		DC	On/off-grid			Cabinet
Sinexcel	PWS/PWG series										
Kehua	BCS series										

Note: There are other compatible test with other brands under process. updating will be made when finishing.